



Unattended Payment Terminal **NEW5310**

- Qualcomm Quad-core CPU
- 5.0" HD IPS display
- Magnetic Card Reader, IC Card Reader, NFC, QR code
- Supports WiFi, 4G, GPS



High Performance
Processor



Asmart



Bank Card



Ip65 & IK08
Protection



4G



NEW5310

Specifications



Bank Card



Ip65



Ik08

CPU

Quad-core

OS

Asmart

Buttons

1 key for reset
1 key for setup menu

Ingress Protection

Ip65

Dimensions

L×W×H (mm):
158.9×93.8×46.5

Memory

1GB RAM+8GB ROM
Supports Micro TF Card,
up to 32GB.

Wire communication

Ethernet (8P8C) RS232 (6P6C,
with power output 12V/0.5A)
Micro fit 43045, power input
socket. MDB (24~45 VDC),
USB Host USB Device

Audios

1 Built-in speaker

Shock Protection

Ik08

Weight

710g

Display

5.0"HD
720x1280 Pixels

Card Slots

1×SIM
1×SAM
1×SD Card

Power Supply

12V DC, 2A
(when using Micro fit)
24 ~ 45V DC
(when using MDB)

Working Environment

Temperature:
-20 °C~60 °C(-4°F~140°F)
Humidity:
5%~90% (non-condense)

Certifications

PCI PTS 5.x, EMV, PBOC, CE, FCC,
RoHS, IP65 /ANSI UL 94V-0 , Ik08,
American express, Discover, JCB,
PayPass, PayWave

Communication

Wi-Fi, 4G(optional)
RS-232, Ethernet 10/100M
MDB

Camera

2MP, Reads 1D & 2D Codes

Flammability Rating

ANSI/UL 94 V-0

Storage Environment

Temperature:
-25°C~70°C(-13°F~158°F)
Humidity:
5% ~95% (non-condense)



The configuration and parameters listed on the product page above are subject to the actual product and are subject to change without notice.

Tel: +86-755-86717417 Fax: +86-755-82790632 E-mail: sales@newpostech.com Web: www.newpostech.com